


## Disola Long Life 10W-40

High performance Long Life engine oil with Low SAPS technology.



| APPLICATIONS                            | FEATURES AND BENEFITS  |
|---|--|
| MAN 175D Engines.                       | Approved for extended drain Intervals of 4000 hours (< 0.1 % fuel sulfur content), and 2000 hours (0.1 - 0.5 % fuel sulfur content), allowing to improve your engine's Total Cost of Ownership (TCO).                |
| Engines requiring long drain intervals. | Disola Long Life 10W-40 is formulated using premium quality base oil together with latest generation additives that provide enhanced piston cleanliness and lubrication performance allowing longer drain intervals. |

| VALIDATIONS AND APPROVALS |                               | MEETS THE REQUIREMENTS OF |                                | INTERNATIONAL STANDARDS |                                   |
|---------------------------|-------------------------------|---------------------------|--------------------------------|-------------------------|-----------------------------------|
| ~                         | MAN 175D Long Drain Intervals | ~                         | MAN M 3477 / M 3271-1          | ~                       | API CK-4/CJ-4/CI-4 Plus/CI-4/CH-4 |
| ~                         | MAN M 3775                    | ~                         | Caterpillar ECF-3/ECF-2/ECF-1a | ~                       | ACEA E6/E7/E8/E9/E11              |
| ~                         | MTU Category 3.1              |                           |                                | ~                       | JASO DH-2                         |
| ~                         | Volvo Penta VDS.4-5           |                           |                                |                         |                                   |
| ~                         | Cummins CES 20086             |                           |                                |                         |                                   |

| TECHNICAL DATA : Disola Long Life 10W-40 |             |         |                 |  |  |  |
|--|-------------|---------|-----------------|--|--|--|
| CHARACTERISTICS                          | METHODS     | UNITS   | TYPICAL VALUES* |  |  |  |
| Density at 15°C                          | ASTM D 4052 | kg/m³   | 867             |  |  |  |
| Kinematic Viscosity at 40°C              | ASTM D 445  | mm²/s   | 96              |  |  |  |
| Kinematic Viscosity at 100°C             | ASTM D 445  | mm²/s   | 14.2            |  |  |  |
| Viscosity Index                          | ASTM D 2270 | _       | 162             |  |  |  |
| Flash Point (COC)                        | ASTM D 96   | °C      | > 230           |  |  |  |
| Pour Point                               | ASTM D 92   | °C      | - 45            |  |  |  |
| Sulfated Ash                             | ASTM D 874  | % m/m   | < 1.0           |  |  |  |
| BN                                       | ASTM D 2896 | mgKOH/g | 10              |  |  |  |

<sup>\*</sup>The specifications above are for illustrative purposes and communicated for information only.





| CUSTOMER BENEFITS |  |  |  |  |
|-------------------|--|--|--|--|
| ~                 | High performance "Low SAPS" (Low content of Sulphated Ash, Phosphorus and Sulphur) oil for high speed applications.  |  |  |  |
| ~                 | Thanks to its "Low SAPS" technology, Disola Long Life 10W-40 is designed for the latest Diesel engines equipped with post-treatment systems, such as Diesel particulate filters (DPF). |  |  |  |
| ~                 | Disola Long Life 10W-40 exhibits excellent thermal stability ensuring efficient lubrication of hot engine parts during severe and long working periods.                                |  |  |  |
| <b>/</b>          | The product belongs to the new "very long drain interval" engine oil generation.   |  |  |  |
| ~                 | Best in class performance, with the longest drain intervals for MAN 175D engines.  |  |  |  |

## **GENERAL RECOMMENDATIONS**

## COMPATIBILITY

Please consult your Lubmarine Lubrication Engineer should you have any questions.

## STORAGE

This product should be stored under cover in clean, dry conditions and protected from frost.

| COMPLIMENTARY PRODUCTS AND SERVICES |   |  |  |
|-------------------------------------|---|--|--|
| ~                                   | Glacelf Auto Supra — Very long life antifreeze based on high purity monoethylene glycol and organic corrosion inhibitors.             |  |  |
| ~                                   | Glacelf MPG Supra — Antifreeze based on monopropylene glycol and organic corrosion inhibitors for heating and cooling circuits.       |  |  |
| V                                   | WT Supra – Innovative and environmentally friendly cooling system inhibitor concentrate.  |  |  |
| V                                   | LubDiag – Oil Analysis – Laboratory based used oil analysis program.  |  |  |
| ~                                   | LubInsight – Suite of onboard testing equipment.  |  |  |
| ~                                   | LubSkills – Lubmarine Engineers are on hand at worldwide locations to assist with lubrication concerns.                               |  |  |
| <b>~</b>                            | Lube On Ship – Visualize your lubricants needs aboard Lubmarine's innovative virtual vessel. lubmarine.totalenergies.com/lube-on-ship |  |  |



