



### Description

'Zinc and chlorine free' engine lubricant non-corrosive to silver alloy metals.

### Applications

Diesel engines built by the Electro Motive Division (EMD) of General Motors running on Gas Oil.

## Auxiliary Mineral Lubricants

### Approvals

E.M.D. (Electro Motive Division of General Motors).

### Features and Benefits

- + API service : CF.
- + No corrosive to silver metals.
- + Excellent detergent properties at high temperatures.
- + Good dispersant properties.
- + Very high anti-wear protection.

### Typical Characteristics

	Methods	Units	SAE40
S.A.E. Grade			40
Kinematic viscosity at 40°C	ISO 3104	mm <sup>2</sup> /s	154
Kinematic viscosity at 100°C	ISO 3104	mm <sup>2</sup> /s	15.1
Flash Point (COC)	ASTM D 92	°C	> 220
Pour Point	ISO 3016	°C	- 12
BN	ASTM D 2896	mgKOH/g	13
Zinc content		ppm	< 10

Characteristics of this chart are indicative typical values.

### ⚠ Handling, Health & Safety

Lubricants consisting of highly refined mineral oils with specific additives. In normal conditions of use, these lubricants present no particular toxic hazard. All lubricants, of any kind, should always be handled with great care, particularly avoiding any contact with the skin. Prevent any risk of splashing, and keep away from combustible materials. Store under cover and away from any risk of contamination.

A safety data sheet complying with current legislation is available at: [www.quickfds.com](http://www.quickfds.com) and [www.totallubmarine.com](http://www.totallubmarine.com)